

inTLCFSIP2MP36 inTLCNSIP2MP36 inTLCBSIP2MP36

Teller Camera Series





















The **Remote Alert** Teller Cameras are designed for applications where high resolution close ups are required of individuals during transactions.

The cameras are mounted in aesthetically pleasing housings that can easily be mounted at payment windows, teller points, desks/counters or other locations where transactions or information exchange may take place.

Applications:

- Banking
- Retail
- Customer Services desks
- •

Features:

- Blank Plate, FDIC or NCUA regulatory signage options.
- Desk Top Mounting
- 3.6mm Lens
- Capture Full Facial images
- 2.1 Mega Pixel Sensor
- Full HD 2MP Image

- Car Rental
- Airline Security
- Licensing
- Triple Stream (H.264/MJPEG/MPEG4)
- Max 30 FPS
- D-WDR
- Simple Web interface
- Onvif Support
- 12VDC or PoE



	Image Sensor	2.1 MP Sensor
System	LED's	Power / Lan
Video	Compression	H.264 / M-JPEG /MPEG4
	Resolution	1920x1080, 1280x720, 720x576, 640x360, 320x180
	Stream	Triple Stream H.264 x 1, M-JPEG x 1, MPEG4 x1
	Bit rate type	Constant(CBR), Variable(VBR)
	Bit Rate	128~8192
	Frame rates	Up to 30fps
	Image Quality	1~99
	Interface	Network Output
	Sensitivity	0.01 Lux
	S/N Ratio	>52dB
	Day/Night	Yes
Lens	Focal Length	3.0mm
Image	Function	Color or Black & White
		Saturation, Contrast, Brightness, Sharpness, Hue, Denoise
Network	LAN Interface	10/100 BaseT Ethernet Auto Sensing
	Protocols	RTP/RTSP, Unicast RTP, Multicast RTP
	ONVIF	ONVIF Version 2.4
Viewer	Browser	IE
Security	Password	Multi-level user access with password protection
Power	Power Consumption	12VDC ±10% 4W max or PoE
Installation/		Configure by Installation wizard
Maintenance	T	,
Operating	Temperature	0°C ~ 50°C (32°F ~ 122°F)
Environments	Humidity	Less than 90%, non condensing
Physical	Dimensions (inch)	4.5"H x 8.5" W x 2.094"D
	Weight	1.2lbs
Order Codes	Signage	inTLCFSIP2MP36 inTLCNSIP2MP36 inTLCBSIP2MP36

Remote Alert reserves the right to amend specifications and design without prior notice