

in11S7N2D



4-in-1, WDR, CS Mount, SDN, Box Camera

4-in1
TVI/CVI
AHD
Analog

Full 1080P
2MP
HD Mode

800TVL
Analog
Mode

SDN
WDR



CS
Mount

24VAC
12VDC

The Remote Alert in11S7N2D is the next generation in our line of ultra compact WDR box cameras. This new model uses the latest in WDR multi performance chipsets . Offering 1080P resolution in HD analog mode or 800TVL in standard analog mode., new Wide-D WDR performance combined with 3D Digital Noise Reduction, this compact camera will produce high quality video in the varying lighting conditions experienced in modern installations. The in11S7N2D series is very compact and flexible enough to meet any installation requirement.

- Compact Die Cast Aluminium Case
- Thermal Management
- Mega Pixel Sensor
- Ultra High 800 TVL in Analog Mode
- Full 1080P HD Mode
- Selectable output, TVI, CVI, AHD or Analog
- Software Day/Night Function
- Min. Illumin. 0.03 Lux
- Wide Dynamic Range (WDR) 130db
- Backlight Compensation (BLC)
- Highlight Compensation (HLC)
- DEFOG
- 2D/3D DNR
- Sense Up
- Manual Iris Only
- Selectable Shutter Speeds
- ATW / AWC White Balance
- CVBS Analogue Video Output
- OSD Menu
- Privacy Zones
- Motion Detection
- Rear Panel Joystick
- CS mount with adjustable back focus control
- 12VDC/24VAC (D Model)

	System	NTSC	
Imaging	Sensor	1/2.8 2MP Advanced Sensitivity Sensor	
	Effective Pixels	1920 x 1080	
Performance	Resolution HD	1080P Full HD	
	Resolution Analog	800TVL	
	Sensitivity	0.03Lux	
	Wide Dynamic Range	130dB Max	
	S/N Ratio	52dB	
	Day / Night	Software Controlled	
Lens	Type	Manual Iris Only	
	Mount	CS (C with Adaptor)	
Functions	Video Interface	Analog HD (TVI, CVI, AHD) & CVBS Analog	
	OSD	English, Chinese, Japanese, Korean	
	Flickerless	On/Off	
	Wide Dynamic Range	On/Off low/Middle/High	
	DEFOG	Auto/Manual/Low/Medium/High	
	Digital Image Stabilize	Yes	
	AGC	Adjustable Level	
	SENS UP	Adjustable Level 512x	
	Electronic shutter	Off/On 1/200,000 sec maximum	
	Sync	Internal	
	Camera ID Number	Off/On 1~255	
	Camera Name	Off/On, 15 Characters	
	White Balance	ATW/Push/Manual	
	DNR	2D + 3D Off, Low, Medium, High	
	Gamma	0.35, 0.4, 0.45, 0.5, 0.55	
	Motion Detection	4 areas, Off/On, Position & Sensitivity	
	Privacy masking	8 areas, Off/On, Color, Position	
	Image functions	Sharpness, Mirror, Flip, D-Zoom	
	Input/Output	Video Output	CVBS 1.0Vp-p 75Ω - BNC
		Programming interface	in-line joystick
Power	D Model	12VDC/24VAC ±10% 4.2W max	
Physical	Construction	Die Cast	
	Dimensions (mm)	40 x 40 x 73	
	Weight	220G	
	Mounting	1/4 20	
Environmental	Operating Temperature	-10°C~+50°C	
	Humidity	Less than 90%, non condensing	
Order Codes		in11S7N2D	



We reserve the right to amend specifications and design without prior notice