

inTLCFS7N2D30
inTLCNS7N2D30
inTLCBS7N2D30

4-in-1 WDR Teller Camera Series



4-in1
TVI/CVI
AHD
Analog

Full 1080P
2MP
HD Mode

800TVL
Analog
Mode

SDN
WDR

24VAC
12VDC

SENS
UP

The **Remote Alert** Teller Cameras are designed for applications where high resolution close ups are required of individuals during transactions.

The cameras are mounted in aesthetically pleasing housings that can easily be mounted at payment windows, teller points, desks/counters or other locations where transactions or information exchange may take place.

Applications:

- Banking
- Retail
- Customer Services desks
- Car Rental
- Airline Security
- Licensing

Features:

- Blank Plate, FDIC or NCUA regulatory signage options.
- Desk Top Mounting
- 3.0mm Lens
- Ultra High 800 TVL in Analog Mode
- Full 1080P in HD Mode
- Selectable Output TVI, CVI, AHD, Analog
- Software Day/Night Function
- Min. Illumin. 0.03 Lux
- Wide Dynamic Range (WDR) 130db
- Backlight Compensation (BLC)
- Highlight Compensation (HLC)
- DEFOG
- 2D/3D DNR
- Sense Up
- Selectable Shutter Speeds
- ATW / AWC White Balance
- OSD Menu
- Privacy Zones
- Motion Detection
- 12VDC or 24VAC



	System	NTSC
Imaging	Sensor	Mega Pixel Sensor
	Effective Pixels	1920 x 1080
Performance	Resolution HD	1080P Full HD
	Resolution Analog	800TVL
	Wide Dynamic Range	130dB Max
	Sensitivity	0.03Lux
	S/N Ratio	52dB
	Day / Night	Software Controlled
Lens	Type	Fixed
	Focal Length	3.0mm
Functions	Video Interface	Analog, HD Mode TVI, CVI AHD
	OSD	Multiple Language
	Flickerless	On/Off
	Wide Dynamic Range	Off/Low/Medium/High
	HLC (High Light Supp)	Off/Low/Medium/High
	BLC (Back Light Comp)	Off/Low/Medium/High
	DEFOG	Off/Low/Medium/High
	AGC	Off/Adjustable Level
	Sens Up	Adjustable level
	Electronic shutter	YES
	Sync	Internal
	Camera ID Number	Off/On 1~255
	Camera Name	Off/On, 15 Characters
	White Balance	ATW/Push/Manual
	DNR	2D + 3D Off/Low/Medium/High
	Gamma	0.35~0.55
	Motion Detection	4 areas, Off/On, Position & Sensitivity
Privacy masking	8 areas, Off/On, Color, Position	
Image functions	Flip, Mirror, D-Zoom	
Input/Output	Video Output	CVBS 1.0Vp-p 75Ω
	Programming interface	Controller
Power	Voltage	12VDC or 24VAC ±10 %
	Power	4.2W Max.
Environmental	Operating Temperature	-10°C~+50°C
	Humidity	Less than 90%, non condensing
	Dimensions	4.5''H x 8.5'' W x 2.094''D
	Weight	1.2lbs
Order ID	FDIC	inTLCFS7N2D30
	NCUA	inTLCNS7N2D30
	BLANK	inTLCBS7N2D30

Remote Alert reserves the right to amend specifications and design without prior notice